



## QINEO QN-WD-AR

### **Strong 4-roller wire drive unit to be mounted to a welding robot**

The robust compact wire drive unit is designed for the use at the welding robot. It has a stable, protective housing that accommodates the drive motor as well as its controller and power transmission mechanics. The precise 4-quadrant controller and high motor power ensure optimum traction and accuracy of the wire feed. Large roller diameters give the wire drive a high traction. This guarantees optimum ignition properties and a consistently high weld quality.

- Excellent welding results due to a powerful and slip-free wire feed
- Precise motor controller ensures optimum ignition properties and a stable arc
- High-quality components guarantee maximum availability
- Stable, compact metal housing protects all relevant parts from external influences





## QINEO QN-WD-AR

### Technical Data

Construction form	External wire drive
Wire feed speed	max. 30 m/min
Dimensions L/W/H	320/200/200 mm
Weight	7.5 kg
Wire diameter	0.8 - 2.0 mm

### Application

Auto

### Process

- MIG Bracing
- MIG/MAG Single Wire AC
- MIG/MAG Single Wire
- MIG/MAG Single Wire pulse

### Questions about the product?

Your contact partner:  
Daniel Weber  
Tel.: +49 (0)2773 85-430  
gt-sales@cloos.de



Technical modifications reserved  
Version: 13.05.2024

CLOOS