



QINEO GLW 502 AC/DC

TIG AC/DC welding power source up to 460 ampere for automated and manual welding

With its excellent process functions, you can use the QINEO GLW-502 TIG Inverter welding power source for a wide range of applications in manual and automated welding. The QINEO GLW provides three different AC waveforms. In this way you always react appropriately to the special requirements of welding aluminium materials. An optional interface offers an optimal connection to robot or system controllers. The high tolerance to mains voltage fluctuations guarantees best welding results with long cable lengths and when operating on a generator. Equipped as standard for gas-cooled TIG welding torches, the units can optionally be equipped with a cooling module. A trolley and a gas bottle holder are also available for an optimum mobility.

- Safe arc ignition: Matched start parameters for best ignition conditions
- Alternating current waveform for every need: Individual AC waveforms for demanding tasks
- Penetration function for thin/thick plate joints: Joining of aluminium plates of very different thicknesses
- Suitable for MMA welding: Optimum flow behaviour and more protection due to VoltageReduceControl
- Optimum power and weight ratio The powerful but light partner - everywhere
- Everything at a glance: A clear operating panel for easy handling
- Robust construction: High level of stability of the devices
- Automation interface: Easy integration of the TIG welding power source in robot welding systems





QINEO GLW 502 AC/DC

Technical Data

Welding current	5 A - 500 A
Welding current 100% duty cycl	400 A
Open circuit voltage	85 V
Mains voltage	400V / 50Hz / 3 phases
Connection cable	4 x 6 mm ²
Type of protection	IP 23 S
Dimensions (L/W/H) compact uni	690 x 290 x 450 mm
Weight compact unit	54 kg

Application

Manual

Process

- TIG AC/DC
- TIG DC

Questions about the product?

Your contact partner:
Daniel Weber
Tel.: +49 (0)2773 85-430
gt-sales@cloos.de



Technical modifications reserved
Version: 10.05.2024

CLOOS